



This two-cable antenna combines two applications at a time: GPS on one cable and any one of several wireless data applications on the other cable.

with GPS

The LMW Series stands out from the other Mobile Mark Surface Mount Antenna Series in that it is extremely broadbanded and covers LTE-U cellular bands from 695-960 MHz and 1710-6000 MHz. It has excellent performance characteristics and performs well across the entire band.


This new wideband Surface Mount Antenna offers greater flexibility for stocking and installation because it can function over multiple systems.

For GPS, the performance is 26 dB amplifier gain with 5 dBi RHCP nominal antenna gain. The antennas have low noise figure with excellent filter characteristics.

This rugged antenna can be mounted with complete confidence in a wide range of settings. It can be mounted to any vehicle, container or bulkhead with a threaded stud mount. For optimal performance, a groundplane is recommended.

Low Profile LTE-U, with GPS 695-960/1710-6000 MHz

- Multiband antenna for Cellular LTE-U and GPS
- Can be used for Mobile LTE-U applications
- For optimal performance, a ground plane is recommended



Specifications			
Frequency:		Standard Cables:	
Cable 1, LTE-U	695-960/1710-6000 MHz	Cable 1	LL-195 15 ft (4.5 m)
Cable 2, GPS	1575.42 +/- 2 MHz	Cable 2 (GPS)	RG-174, 15 ft (4.5 m)
Data Side:		Optional Cables:	
Gain (695-960 MHz)	Unity	Cable 1	RG-58, 15 ft (4.5 m)
Gain (1710-6000 MHz)	3-5 dBi		
VSWR:	<2.5:1 max over range	Connectors:	SMA Plug (Male) standard
Nominal Impedance:	50 Ohm	Case:	3.5"D x 1.5"H (8.9 cm x 3.8 cm)
Power:	10 Watts	Case Material:	UV resistant ASA
Operating Temp:	-40° to +80° C	Mounting:	5/8" dia.x 3/4" long
			(1.6 cm x 1.9 cm)
GPS Side:			Up to 1/2" (1.27 cm) thick metal
Amplifier gain	26 dB. LNA	Hardware:	Nut and gasket included
Antenna gain	5 dBi nominal RHCP, Antenna		
Noise Figure	2.0 dB max, 1.7 dB typical	Water Ingress:	IP67
Amplifier Bias	2.7 to 5 VDC		
Amplifier Current	20 mA max, 10 mA typical	Shock & Vibration:	EN 61373, IEEE 1478,MIL-810G
•	, , , , , , , , , , , , , , , , , , , ,		