

LTMG301

MULTIBAND SURFACE MOUNT ANTENNA

PRODUCT OVERVIEW

The 3-cable LTMG301 contains elements for two Cellular antennas and one GNSS antenna. It provides MIMO (multiple-input-multiple-output) coverage for Cellular up to 2170 MHz. It is recommended that users of the LTMG301 switch to the LTM302 which goes up to 3700 MHz. This antenna can be used for fleet management systems that combine GNSS with an LTE MIMO modem. GNSS operates on GPS, Galileo, Glonass, QZSS, or Beidou.

Specify LTM for units with GPS and LTMG for units with GNSS.

Specify MLTMG or MLTM for Mag Mounted units.

Specify CLTM or for Ceiling Mounted units.

Visit our [eStore](#) to purchase an Antenna Online.



L T M G 3 0 1 - 3 C 3 C 2 C - B L K - 1 8 0



Electrical Specifications		
Frequency & Gain	LTE Cables 1 & 2	694 - 960 MHz, 3 dBi 1710 - 2170 MHz, 4 dBi
	GNSS Cable 3	1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBic (RHCP)
VSWR	< 2:1 VSWR Over Range	
Impedance	50 Ohm Nominal	
Power Rating	10 Watts	
GNSS	Amplifier Gain	26 dB +/- 3 dB
	Amplifier Bias Voltage	2.7 to 5 VDC
	Noise Figure	2.0 dB max, 1.5 dB typical
	Current	20 mA max, 10 mA typical

Mechanical Specifications	
Radome Material & Color	ASA UV-Inhibitive Plastic, Available in Black or White
Radome Base Material	Corrosion Resistant Aluminum
Radome Dimension	5.50" (139 mm) in Diameter & 2.38" (60 mm) in Height
Optional Mag-Mount	add 0.5"(13 mm) for height dimension
Standard Connectors	SMA Plugs (Male)
Cables 1 - 2	Separate LL-195, 15 ft (4.5 m)
GNSS Cable 3	RG-174, 15 ft (4.5 m)
Operating Temperature	-40° to +80° C
Mounting	7/8" (22 mm) Dia. Feed Through 3/4" (19 mm) Ig. Thread for up to 1/2" (13 mm) Thick Surface
Shock & Vibration	IEEE-1478, EN 61373, MIL-810G, TIA 329.2-C
Dust & Water Ingress	IP69K (Stud Mount, When Properly Mounted)
	IP67 (Mag-Mount, When Properly Mounted)
RoHS Compliant	Yes

HIGHLIGHTS:

- Multiband Surface Mount: 2x LTE & 1x GNSS
- Covers 694 - 2170 MHz
- High Performance; High Gain
- Made-in-the-USA & UK

RELATED MODELS:

- LTMG302 (upgrade to 3700 MHz)
- CLTM302 (Ceiling Mount Model)
- MLTMG302 (Mag Mount Model)

COMMON APPLICATIONS:

- Vehicle Fleet Management
- Multiband Modems
- Public Transportation



US Headquarters +1.847.671.6690 • US/CA Toll Free +1.800.648.2800
European Facility +44.1543.459555 • www.MobileMark.com

Moving Wireless Forward®