

PRODUCT OVERVIEW

The X-WAV™ 2.4 GHz (802.11b/g) Flat Panel Sector antennas deliver an ideal solution for a wide range of Wi-Fi applications. Utilizing Luxul's Clear-WAV™ technology for delivering superior performance characteristics, the Flat Panel series combines high performance with a sleek, low profile design. It is a highly reliable and cost effective alternative to traditional antenna technologies. The X-WAV Flat Panel series provides an ideal solution for sector coverage as well as medium and long range Point-to-Point and Point-to-Multipoint links. X-WAV antennas offer the performance benefits of Circular Polarization technology, including superior signal propagation and penetration, with less susceptibility to outside interference and multipath signals. X-WAV antennas can be used in conjunction with most commercially available Wireless Access Points (WAPs) and Customer Premise Equipment (CPE) to deliver a more powerful signal propagation solution. Additional benefits include superior connectivity and signal alignment, and the enhanced ability to connect users on the outer edges of a network.

Results may vary depending on environmental factors, interference, cable length and type, etc.

Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

FCC Notice: The use of all radio equipment is subject to regulations in each country. To comply with FCC part 15 rules in the United States, radio equipment must only be used in systems that have been FCC certified. It is the responsibility of the user, professional installer, operator to ensure that only approved equipment, systems are deployed.

X-WAV™ 2.4GHz SECTOR ANTENNA

XW-24O-FPS11



The X-WAV™ Antenna family implements Clear-WAV™ Circular Polarization technology for increased signal penetration, less interference and extended wireless coverage. X-WAV antennas are widely implemented and recommended for use in mobile and Non-Line-of-Site (NLOS) applications. The Circular Polarization of the X-WAV signal pattern allows for superior penetration of obstacles such as trees, walls, and buildings. Other benefits include less susceptibility to multipath interference or noisy signals and enhanced interoperability with conventional systems.

Specifications	
Part Number	XW-24O-FPS11
Frequency Range	2400 - 2500 MHz
Gain	11 dBi
Polarization	Clear-WAV Right Hand Circular
Connector	N Female
Azimuth Beam Width	70 degrees
Elevation Beam Width	36 degrees
VSWR	< 1.5:1
F/B Ratio	19 dB
Impedence	50 Ohm
Dimensions	W: 4.25" (107.95mm), L: 7.25" (184.15mm), H: 1.6" (40.64mm)
Weight	6.5 oz (184.3g)
Radiation Pattern	
Application	For sector coverage and medium to long range point-to-multipoint links

PRODUCT SHIPS WITH:

Antenna, HDW-AM-UOD outdoor mounting bracket, Quick Install Guide

Luxul Antennas now a Mobile Mark Inc. Brand